

# **400 Mbps Bandwidth Management Device**

Allot NetEnforcer® AC-500 manages Internet traffic on multiple Ethernet links at speeds of up to 400 Mbps. This flexible device brings carrier-class functionality and reliability to enterprise networks, providing real-time analytics, policy enforcement, and security services.



## **Features**

- Throughput of 10, 50, 100, and 200 Mbps (full duplex) with real-time analytics and Quality of Service (QoS) management of up to 400,000 concurrent IP flows
- Interface options support a variety of network topologies:
  - 2 x 10/100/1000Mbps Ethernet ports (1 link) + 2 ports for cascading, high availability
  - 4 x 10/100/1000Mbps Ethernet ports (2 links) + 4 ports for cascading, high availability
- IPv4/IPv6 dual stack subscriber support for flexible network configuration
- Powered by Allot's Dynamic Actionable Recognition Technology (DART) engine, which provides granular visibility of user, application, device (including tethering), and network topology traffic
- DART's extensive signature library accurately identifies hundreds of Internet applications and protocols, including P2P, VoIP, streaming, gaming, instant messaging, web, and enterprise applications

- Automated, web-based update keeps the signature library up to date with the latest developments
- Supports user-defined signatures based on HTTP attributes, as well as monitoring reports based on custom HTTP signatures
- Real-time analytics and automatic alarms enable fast and accurate troubleshooting with the ability to trigger corrective actions
- Works together with Allot Subscriber Management Platform (SMP) to provide real-time usage data for online and offline charging and subscriber policy management
- Integrated URL filtering service blocks access to blacklisted and illegal web sites at the network level (see Allot WebSafe)
- Integrated threat protection system prevents DNS blacklisting, isolates infected botnet hosts for clean-up, and surgically mitigates DDoS attacks (see Allot ServiceProtector)
- Managed by Allot NetXplorer centralized management system



### **Specifications**



Allot NetEnforcer AC-500 Series is available in two models serving a range of network configurations and needs.

		AC-502	AC-504
Capacity	Throughput	400 Mbps (200 Mbps full duplex)	
	Number of Connections/Flows	200,000/400,000	
	Number of Subscribers	32,000	
	Lines/Pipes/Virtual Channels	Up to 512 / 8,192 / 32,768	
Interfaces and	Management Interface	10/100/1000BASE-T	
Connections	Network Interfaces (Internal / External)	2 x 10/100/1000BASE-T	4 x 10/100/1000BASE-T
	Cascading/Redundancy	2 x 10/100/1000BASE-T	4 x 10/100/1000BASE-T
	Console Port	Serial, RJ-45 Connector	
Examples of	P2P	Including BitTorrent, eDonkey, Ares, Gnutella, Thunder, eMule, Vuze, Winny	
Application/Protocol Signatures Supported	VoIP and IM	Including Windows Live Messenger, SIP, Skype, Yahoo Messenger, GoogleTalk, Fring, WhatsApp, , STUN, ICQ, Viber, and QQ	
	Gaming	Including World of Warcraft, Final Fantasy, Guitar Hero, Second Life, QQ Games, Lineage, CounterStrike, Call of Duty, Apple Game Center	
	Web	Including HTTP, mobile, and social networking applications	
	Streaming	Including YouTube, RTMP, QQ live, PPStream, DailyMotion, HTTP streaming, HTTP audio, NetFlix, and Facebook streaming	
	File Transfer	Including FTP, HTTP file downloads, Apple App Store, Android Market	
Networking	Traffic Encapsulation	Including L2TP, MPLS, PPPoE, and Teredo IPv6 subscriber management available with Allot SMP	
Standards	IPv6		
Product Options	QoS Enforcement Levels	10, 50, 100, and 200 Mbps full duplex	
	Analytics (Monitoring and Reporting)	Real-time and long-term	
	High Availability	Active redundancy (1:1, 1+1)	
Full Integration with Allot Digital Lifestyle Services	Allot Subscriber Management Platform (SMP)	For centralized creation, provisioning, and charging of per-subscriber services	
	Allot ClearSee Analytics	For capturing rich source data from the network and transforming it into valuable business intelligence	
	Allot WebSafe	For URL filtering solutions at the network level	
	Allot ServiceProtector	For DDoS/outbound spam detection and mitigation solutions	
Dimensions	Size / Weight	Standard 1U by 19" rack mount / 4.24 kg ( 9.35 lb)	
	Dimensions / Operating Temp	300mm x 440mm x 44mm (L x W x H) / 0°C to 50°C	
	Bypass Unit	Internal	
Power	Input (AC)	100-240 VAC. 50/60Hz, 2A max	
	Power Supply Unit	80W	90W
	Heat Dissipation	274 BTU/hour	308 BTU/hour
Safety and	CE Conformity	Directive 2004/108/EC, Directive 2006/95/EC	
Certifications	Safety	UL 60950-1:2007 EN 60950-1:2006 / A11:2009 CAN/CSA-C22.2 No. 60950-1-07	
	EMC	European Directives 2004/108/EC & LVD 73/23/ EEC EN 55022: 2006 EN 55024:98 + A1: 2001 + A2: 2003 ETSI EN 300 386 V1.3.3:2005-04 FCC CFR 47 Part 15 Subpart B Industry Canada ICES-003:04; C108.8-M1983 VCCI Class A Technical Requirements, V-3/2001.04 Australia ACMA, AS/NZS CISPR22:2006	
	RoHS/WEEE Compliance	Directive 2002/95/EC (RoHS) Directive 2002/96/EC (WEEE)	

#### (i) About Allot Communications

Allot Communications Ltd. (NASDAQ, TASE: ALLT) is a leading global provider of intelligent broadband solutions that put mobile, fixed and enterprise networks at the center of the digital lifestyle and workstyle. Allot's DPI-based solutions identify and leverage the business intelligence in data networks, empowering operators to analyze, protect, improve and enrich the digital lifestyle services they deliver. Allot's unique blend of innovative technology, proven know-how and collaborative approach to industry standards and partnerships enables network operators worldwide to elevate their role in the digital lifestyle ecosystem and to open the door to a wealth of new business opportunities. For more information, please visit www.allot.com  $\,$ 

#### sales@allot.com

Americas: 300 TradeCenter, Suite 4680, Woburn, MA 01801 USA Tel: +1 (781) 939-9300 Fax: +1 (781) 939-9393 Toll free: 877-255-6826 ● Europe: NCI – Les Centres d'A\_aires Village d'Entreprises 'Green Side', 400 Avenue Roumanille, BP309, 6906 Sophia Antipolis Cedex, France Tel: +33 (0) 4-93-001160, Fax: +33 (0) 4-93-001165 ● Asia Pacific: 25 Tai Seng Avenue, #03-03, Scorpio East Building, Singapore 534104 Tel: +65 67490213 Fax: +65 68481015 • **Japan**: 4-2-3-301 Kanda Surugadai, Chiyoda-ku, Tokyo 101-0062 Tel: +81 (3) 5297-7668 Fax: +81(3) 5297-7669 • **Middle East and Africa**: 22 Hanagar St., Industrial Zone B, Hod-Hasharon, 4501317, Israel, Tel: +972 (9) 761-9200, Fax: +972 (9) 744-3626



P/N D240031 Rev.4