

Allot High Performance Platforms

Service Gateway 9500



Powering the Digital Experience

Allot Service Gateway 9500 provides a powerful service delivery platform in an Intel-based appliance, designed especially for cloud data center, enterprise, and ISP networks. Its small footprint is equipped with the same rich features and functions as the chassis-based Allot Service Gateway, enabling you to roll out Security as a Service as well as other revenue-generating services rapidly and cost-effectively, while you lower your total cost of ownership and accelerate ROI.



Highlights

- Powerful and cost-efficient service delivery platform
- 140 Gbps per appliance; up to 1 Tbps in a cluster
- Real-time Layer-7 application visibility, policy enforcement, charging
- Real-time visibility of encrypted traffic
- Supporting turnkey Security as a Service solutions
- Deployment and management across any access
- Easy installation and pay-as-you-grow scalability

Features

Single Point of Service Integration

Allot SG-9500 supports Allot's Security as a Service offering as well as a growing portfolio of pre-integrated value-added services including:

- Allot WebSafe Personal (Security as a Service for consumers)
- Allot WebSafe Business (Security as a Service for businesses)
- Allot ServiceProtector (DDoS protection and anti-bot)
- Allot ContentProtector (URL filtering)
- Allot SpamOut Protector (anti-spam service)

The platform also supports real-time traffic steering to third-party applications or virtualized services. As a single point of integration for these services, Allot SG-9500 minimizes interoperability and service integration issues to facilitate fast and efficient service rollout.

Efficient Performance

Allot Service Gateway 9500 (SG-9500) provides a high performance service delivery platform with rich functionality in an efficient, small-footprint appliance. With high-density 10 Gigabit Ethernet connectivity and 140 Gbps of throughput, the platform allows enterprises, cloud data centers and ISP networks to satisfy the ever-growing demand for Internet bandwidth and network-based services in a cost-efficient manner.

Future-Proof Scalability

Start small and expand seamlessly with pay-as-you-grow deployment that reduces initial capital outlay and allows network operators to respond quickly to market changes.

- **Capacity:** supports up to 4 million active users (concurrently attached and active), and 48 million concurrent IP flows
- **Connectivity:** up to 24 x 10 Gigabit Ethernet
- **Throughput:** up to 140 Gbps in a single platform
- **Clustering:** supports up to 8 Allot SG-9500 platforms in a seamless cluster configuration providing aggregate throughput of up to 1 Tbps
- **Central Management** and configuration by Allot NetXplorer Management system, including full integration with Allot Subscriber Management Platform (SMP)

Accurate Traffic Visibility and Policy Control

Allot's Dynamic Actionable Recognition Technology (DART) engine, embedded in the platform, gives you granular visibility of application, user, device, quality-of-experience (QoE) and network topology traffic. Allot's extensive signature library accurately identifies hundreds of Internet applications and protocols, and also supports user-defined signatures. Frequent and automated updates to the signature library keep Allot Service Gateways up to date with the latest applications and Internet developments, ensuring accurate traffic detection and classification.

SDN / NFV Compatibility

Allot Service Gateway 9500 leverages Intel-based hardware to provide a powerful and cost-efficient platform that is ideal for network operators who are in various stages of migration to cloud-based network services and Network Functions Virtualization (NFV)

Allot SG-9500 is able to interface seamlessly with data-plane and control-plane elements in the network. Allot supports proprietary and standard OpenFlow to enable real-time Layer-7 traffic management, policy control, security services and service delivery optimization in software-defined networks (SDN).

Moreover, Allot's flexible and powerful Policy Editor makes it easy for you to provision and enforce real-time Quality of Service (QoS), steering, metering and charging policy with equal granularity.

Efficient Clustering

Allot SG-9500 maintains accurate Layer-7 visibility and control of user-application traffic across multiple platforms even when asymmetric upstream and/or downstream IP flows are processed by different appliances. Clustering of up to eight platforms utilizes dedicated interfaces with very low synchronization traffic overhead.

Intelligent Policy and Charging Enforcement

Compliance with 3GPP standards enables Allot SG-9500 to provide intelligent Traffic Detection Function (TDF) and Policy and Charging Enforcement Function (PCEF) in 3G/4G mobile data networks. As a result, network operators can leverage superior traffic identification and classification to enrich the policy decisions of PCRF elements, and to enhance the charging capabilities of online and offline charging systems (OCS, OFCS).

Collecting Network Data Records

From its vantage point in the network, Allot SG-9500 collects and exports a rich variety of high-resolution usage data, including real-time transactions per user, per application, per device, per video session, per VoIP and Instant Messaging session, per Web session, and more. Network data records may be exported in standard formats to business intelligence systems, such as Allot ClearSee Network Analytics, and other operator systems for further manipulation and analysis. Frequency and triggers for data record export are configurable parameters, giving operators ready access to usage data that is critical to their business. The data records coming from Allot SG-9500 are configurable and may be customized by Allot Data Science Services for any destination or use case requirements.

Specifications

Allot Service Gateway 9500 Platform

| Allot SG-9500 | |
|---|--|
| Capacity | |
| Throughput per Platform | 140 Gbps |
| Throughput per Cluster | 1 Terabit/sec using 8 devices |
| Number of Flows | 48 Million |
| Number of Active Subscribers | 4,000,000 |
| Number of Policy Lines / Pipes / Virtual Channels | 1000 / 800,000 / 4,000,000 |
| Interfaces | |
| Ethernet Interfaces | 24 x 10 Gigabit Ethernet |
| Management | 2 x 10 Gigabit Ethernet or 2 x 1 Gigabit Ethernet |
| Physical Characteristics | |
| Form Factor | 2U 19" rack mount |
| Size | 8.73 x 44.55 x 73.02 cm (3.44 x 17.54 x 28.75 in) , dimensions without Bezel |
| Weight | Min 32.6 lb (14.759 kg), Max 42 lb (19 kg) per number of NIC interfaces |
| Power | Dual Hot Plug, Redundant 100/240VAC or -48VDC, efficiency of up to 94%, Energy star, 80PLUS, 800W |
| Environment | Operating temp 10°C to 35°C (50°F to 95°F), Relative humidity (%RH) 8% to 90% |
| Availability | |
| System Redundancy | Redundancy for PSUs and fans |
| Hardware Bypass | Independent, passive bypass unit |
| Bypass Configuration | Up to two units, HD-8 fiber-optic ports (4 links) Or HD-16 fiber-optic ports (8 links) Or Single unit HD-24 fiber-optic ports (12 links) |
| HD-8 Multi-Port Bypass Unit | External 1U 19" rack mount, 2.44kg (5.38lb) |
| HD-16 Multi-Port Bypass Unit | External 1U 19" rack mount, 2.64kg (5.82lb) |
| HD-24 Multi-Port Bypass Unit | External 1U 19" rack mount, 2.86kg (6.3lb) |



About Allot Communications

Allot Communications (NASDAQ, TASE: ALLT) is a leading provider of security and monetization solutions that enable service providers to protect and personalize the digital experience. Allot's flexible and highly scalable service delivery framework leverages the intelligence in data networks, enabling service providers to get closer to their customers, safeguard network assets and users, and accelerate time-to-revenue for value-added services. We employ innovative technology, proven know-how and a collaborative approach to provide the right solution for every network environment. Allot solutions are currently deployed at 5 of the top 10 global mobile operators and in thousands of CSP and enterprise networks worldwide.

www.allot.com info@allot.com

© 2016 Allot Communications Ltd. All rights reserved. Specifications are subject to change without notice. Allot Communications, Sigma and NetEnforcer and the Allot logo are trademarks of Allot Communications. All other brand or product names are the trademarks of their respective holders.

sales@allot.com

Americas: 300 TradeCenter, Suite 4680, Woburn, MA 01801 USA Tel: +1 (781) 939-9300 Fax: +1 (781) 939-9393 Toll free: 877-255-6826 • **Europe:** NCI – Les Centres d’Affaires Village d’Entreprises ‘Green Side’, 400 Avenue Roumanille, BP309, 6906 Sophia Antipolis Cedex, France Tel: +33 (0) 4-93-001160, Fax: +33 (0) 4-93-001165 • **Asia Pacific:** 25 Tai Seng Avenue, #03-03, Scorpio East Building, Singapore 534104 Tel: +65 67490213 Fax: +65 68481015 • **Japan:** 4-2-3-301 Kanda Surugadai, Chiyoda-ku, Tokyo 101-0062 Tel: +81 (3) 5297-7668 Fax: +81(3) 5297-7669 • **Middle East and Africa:** 22 Hanagar St., Industrial Zone B, Hod-Hasharon, 4501317, Israel, Tel: +972 (9) 761-9200, Fax: +972 (9) 744-3626

